

BIBFRAME AGENT DATA FROM MARC AUTHORITY RECORDS –

IS IT AN UNNECESSARY REDUNDANCY?

Miklós Hubay

LIS PhD Student

Representative of National Széchényi Library


17 September 2019



Hungary – Looking and Evaluating

- Hungarian National Library represented by Miklos Lendvay and Miklos Hubay
 - *Have carried out experiments looking at multiple vocabularies, rdf schema, bibo, etc.*
 - *BIBFRAME offered an opportunity to work with a vocabulary more “in tune” with the library cataloging guidelines*
 - *Examining questions:*
 - Is BIBFRAME well known enough yet?
 - Is there a critical quantity of data using BIBFRAME to spawn tools?

BRIEF HISTORY OF BF:AUTHORITY



```
rdf:about="http://bibframe.org/vocab/Authority">  
<rdfs:subClassOf  
rdf:resource="http://bibframe.org/vocab/Resource" />
```

```
<rdfs:comment>Representation of a key  
concept or thing. Works and Instances,  
for example, have defined relationships  
to these concepts and things.  
</rdfs:comment>
```

BRIEF HISTORY OF BF:AUTHORITY

„**BIBFRAME Authority** is used to identify the following that may be associated with a Work or Instance”

Subclasses

- **Agent** - entity having a role in a resource (Person, Organization, etc.)
- **Place** - geographic location
- **Temporal Concept** - chronological period
- **Topic** - concept or area of knowledge

Properties

- **hasAuthority** – link to controlled form of name or subject and other information about
- **referenceAuthority** – link to authority information
- **authoritySource** – authority list from which a value is taken
- **authorityAssigner** – entity that assigned the information

THE „KISS” VERSION

```
ex:wk666 a bf:Work ;  
bf:creator <http://id.loc.gov/authorities/names/n79049248>
```

THE „LEVEL 2” VERSION

```
ex:wk666 a bf:Work ;
```

```
bf:subject http://bibframe.org/resources/sample-pu/5952219topic14
```

```
[...]
```

```
<http://bibframe.org/resources/sample-pu/5952219topic14> a bf:Topic ;
```

```
bf:authorizedAccessPoint "Color prints, Japanese--Meiji period, 1868-1912" ;
```

```
bf:hasAuthority <http://id.loc.gov/authorities/subjects/sh85028638> ;
```

THE „LEVEL 3” VERSION

ex:wk666 a bf:Work ;

bf:contributor <http://data.libraries.uc.edu/armstrong/bibframe/people/3>
[...]

<http://data.libraries.uc.edu/armstrong/bibframe/people/3> a **bf:Person** ;
bf:authorizedAccessPoint "Armstrong, Neil, 1930-2012" ;
bf:hasAuthority "<http://id.loc.gov/authorities/names/n80008815>" ;

bf:referenceAuthority

"<http://viaf.org/viaf/111826406>" ;


"http://en.wikipedia.org/w/index.php?title=Neil_Armstrong&oldid=650449902" .

bf:label "Armstrong, Neil, 1930-2012" ;

WHAT'S MORE...

- `<http://id.loc.gov/resources/bibs/14920419> a bf:Work ;
bf:authorizedAccessPoint "Maxwell, Robert L., 1957- FRBR :a guide for the perplexed",
"maxwellrobert11957frbraguidefortheperplexedengworktext"@x-bf-hash ;`
- `<http://catalog.coloradocollege.edu/4124646> a bf:Work ;
bf:authorizedAccessPoint "Austen, Jane, 1775-1817. Pride and prejudice / Jane Austen ; with illustrations by Edgard Cirlin.Pride and prejudice",
"austenjane17751817cirlinedgard1913prideandprejudiceengworktext"@x-bf-hash ;`
- `<bf:authorizedAccessPoint
xml:lang="x-bf-
hash">gordonburgess11892americancollegeofchestphysiciansclinicalcardiopulmon
aryphysiologyengworktext</bf:authorizedAccessPoint>`
- `<bf:authorizedAccessPoint>Rinzler, Lodro. The Buddha walks into the office :
a guide to livelihood for a new generation</bf:authorizedAccessPoint>
<bf:title xml:lang="x-bf-sort">Buddha walks into the office :</bf:title>`

EVOLUTION IN BF2



LOC SPECIALITIES IN BFLC

Keep the subfield order
and handle the primary contribution
and...

- **MatchKey** – drop all indicators and subfield codes
- **MarcKey** – keep all indicators and subfield codes with \$ delimiter
- **titleSortKey** – rdfs:label + remove the characters that have been specified in i2

```
name00MarcKey  
name00MatchKey  
name10MarcKey  
name10MatchKey  
name11MarcKey  
name11MatchKey
```

```
primaryContributorName00MatchKey  
primaryContributorName10MatchKey  
primaryContributorName11MatchKey
```

```
title00MarcKey  
title00MatchKey  
title10MarcKey  
title10MatchKey  
title11MarcKey  
title11MatchKey  
title30MarcKey  
title30MatchKey  
title40MarcKey  
title40MatchKey
```

```
titleSortKey
```

```
<rdf:type rdf:resource="http://id.loc.gov/ontologies/bflc/PrimaryContribution"/>
```

```
<bflc:name00MatchKey>Schulz, Charles M. (Charles Monroe), 1922-  
2000.</bflc:name00MatchKey>
```

```
<bflc:name00MarcKey>7001 $aSchulz, Charles M.$q(Charles Monroe),$d1922-  
2000.</bflc:name00MarcKey>
```

VARIATIONS ON A TITLE

```
<bf:authorizedAccessPoint>Rinzler, Lodro. The Buddha walks into the office : a  
guide to livelihood for a new generation</bf:authorizedAccessPoint>  
<bf:title xml:lang="x-bf-sort">Buddha walks into the office :</bf:title>
```

© Billey, 2015

```
<bf:title>  
  <bf:Title>  
    <bflc:title40MatchKey>Az ördög. magyar</bflc:title40MatchKey>  
    <bflc:title40MarcKey>24013$060200$aAz ördög.$lmagyar$960200</bflc:title40MarcKey>  
    <rdfs:label>Az ördög. magyar</rdfs:label>  
    <bflc:titleSortKey>ördög. magyar</bflc:titleSortKey>  
    <bf:mainTitle>Az ördög</bf:mainTitle>  
  </bf:Title>  
</bf:title>
```

WHO IS THE AGENT AMONG US?

1) BIBFRAME Comparison Tool - loaded MARC (BIBID: 99823)

```
<bf:agent >
  <bf:Agent rdf:about="http://id.loc.gov/authorities/names/n2004089059" >
    <rdf:type rdf:resource="http://id.loc.gov/ontologies/bibframe/Person" />
    <bflc:name00MatchKey >Milošević, Žarko.</bflc:name00MatchKey>
    <bflc:primaryContributorName00MatchKey >Milošević, Žarko.</bflc:primaryContributorName00MatchKey>
    <bflc:name00MarcKey >1001 $aMilošević, Žarko.</bflc:name00MarcKey>
    <rdfs:label >Milošević, Žarko.</rdfs:label>
  </bf:Agent>
</bf:agent>
```

Class:	Person
URI:	http://id.loc.gov/ontologies/bibframe/Person
Label:	Person
Definition:	Individual or identity established by an individual (either alone or in collaboration with one or more other individuals).
SubClass Of:	Person  Agent
Change Notes:	2016-04-21 (New)

WHO IS THE AGENT AMONG US?

2) BIBFRAME Editor Workspace - loaded MARC (BIBID: 99823)

```
<bf:agent>  
  <bf:Agent rdf:about="http://id.loc.gov/authorities/names/n2004089059">  
    <rdfs:label>Milošević, Žarko.</rdfs:label>  
    <rdf:type rdf:resource="http://www.loc.gov/mads/rdf/v1#PersonalName"/>  
    <bflc:primaryContributorName00MatchKey>Milošević, Žarko.</bflc:primaryContributorName00MatchKey>  
    <bflc:name00MatchKey>Milošević, Žarko.</bflc:name00MatchKey>  
    <bflc:name00MarcKey>1001 $aMilošević, Žarko.</bflc:name00MarcKey>  
  </bf:Agent>  
</bf:agent>
```


Class:	madsrdf:PersonalName
URI:	http://www.loc.gov/mads/rdf/v1#PersonalName
Label:	Personal Name Type
Comment:	Describes a resource whose label represents a personal name.
SubClass Of:	madsrdf:Name

THERE IS NO PERF...

3) BIBFRAME Comparison Tool - loaded MARC (BIBID: 2271245)

```
<bf:subject >
  <bf:Agent rdf:about="http://bibframe.example.org/2271245#Agent600-18" >
    <rdf:type rdf:resource="http://id.loc.gov/ontologies/bibframe/Person" />
    <rdf:type rdf:resource="http://www.loc.gov/mads/rdf/v1#PersonalName" />
    <madsrdf:authoritativeLabel >Holtorf, Hans, 1899</madsrdf:authoritativeLabel>
    <madsrdf:isMemberOfMADSScheme rdf:resource="http://id.loc.gov/authorities/subjects" />
    <bf:source >
      <bf:Source >
        <bf:code >lcsh</bf:code>
      </bf:Source>
    </bf:source>
    <bflc:name00MatchKey >Holtorf, Hans, 1899-</bflc:name00MatchKey>
    <bflc:name00MarcKey >60010$aHoltorf, Hans,$d1899-</bflc:name00MarcKey>
    <rdfs:label >Holtorf, Hans, 1899-</rdfs:label>
  </bf:Agent>
</bf:subject >
```

MICRO-PROJECT IN NATIONAL SZÉCHÉNYI LIBRARY



SEMANTIC TRADITION OF NSZL



• **Collection catalogue and Digital Library** - RDFDC, FOAF, SKOS, BIBO
+ sameAs to DBPedia (April, 2010)

• **Hungarian Electronic Library** – with Flint SPARQL Editor (2015)
<http://v.mek.oszk.hu/FlintSparqlEditor/index-mek.html>

• **Digital Archive of Pictures** – with Flint SPARQL Editor (2017)
<http://v.mek.oszk.hu/FlintSparqlEditor/index-dka.html>



- **A new data set:** RDA- and entity-based bibliographic (15) and authority records (~50) from KOHA
- BIBFRAME-conversion with BF- and metadata experts
- In Virtuoso
 - now (bib)
 - under construction (aut)

THE PROBLEM OF \$0-S

=100 1\

\$a Molnár Ferenc,

\$d 1878-1952

\$e szerző

\$4 aut

\$0 4016

\$9 4016

```
<rdfs:label>Molnár Ferenc, 1878-1952</rdfs:label>  
<bf:identifiedBy>  
<bf:Identifier>  
<rdf:value/>  
</bf:Identifier>  
</bf:identifiedBy>  
<bf:Agent  
rdf:about="http://data.koha.oszk.hu/#Agent">
```

There were no \$0 values in two records (unintentionally)

THE PROBLEM OF \$0-S

**ID-based URI instead of
entity-based URI**



=**710** 2\

\$a Franklin Társulat
Magyar Irodalmi Intézet
és Könyvnyomda

\$e kiadó

\$4 pbl

\$9 60166

```
<bf:contribution>  
<bf:Contribution>  
<bf:agent>  
<bf:Agent rdf:about="http://data.koha.oszk.hu/233151#Agent">  
<rdf:type  
rdf:resource="http://id.loc.gov/ontologies/bibframe/Organization"/>  
<rdfs:label>Franklin Társulat Magyar Irodalmi Intézet és  
Könyvnyomda</rdfs:label>  
</bf:Agent>  
</bf:agent>
```

***There were no \$0 values at all
(KOHA configuration problem in 700 and 710)***



It's all about URIs...

DATA ENRICHMENT FROM AUTHORITY RECORDS

Adding Birth and Death Date (and Place) as Typed Literals

```
<bflite:dateBirth>value of 046$f</bflite:dateBirth> - or dateStart (046$q)  
<bflite:dateDeath>value of 046$g</bflite:dateDeath> - or dateEnd (046$r)
```

```
<bflite:placeBirth>  
  <bf:Place>  
    <rdf:type rdf:resource="http://id.loc.gov/ontologies/bibframe/Place"/>  
    <rdfs:label>value of 370$a</rdfs:label>  
  </bf:Place>  
</bflite:placeBirth>
```

```
<bflite:placeDeath>  
<  bf:Place>  
    <rdf:type rdf:resource="http://id.loc.gov/ontologies/bibframe/Place"/>  
    <rdfs:label>value of 370$b</rdfs:label>  
  </bf:Place>  
</bflite:placeDeath>
```

DATA ENRICHMENT FROM AUTHORITY RECORDS

Language Informations

```
<bf:language>
  <bf:Language rdf:about="http://id.loc.gov/vocabulary/languages/hun" />
</bf:language>
```

```
<bf:language>
  <bf:Language>
    <rdfs:label>magyar</rdfs:label>
  </bf:Language>
</bf:language>
```


```
<bf:language>
  <bf:Language>
    <bf:identifiedBy>
      <bf:Identifier>
        <rdf:value rdf:resource="http://id.loc.gov/vocabulary/languages/hun" />
      <bf:source>
        <bf:Source rdf:about="http://id.loc.gov/vocabulary/languages" />
      </bf:source>
    </bf:Identifier>
  </bf:identifiedBy>
</bf:Language>
</bf:language>
```

„Language associated with a resource or its parts.”

Resource = **Agent**
based on **377\$a**

Let the range be
bf:Language!

AND FINALLY... THE GREAT DEBATE



© Meehan, 2014



THANK YOU FOR YOUR ATTENTION! :)